

SPECIFICATIONS

i7500 Industrial Label Printer 300 dpi

600 DPI VERSION ALSO AVAILABLE



KEY CHARACTERISTICS

Applications: Asset tracking, Barcode labelling, Circuit board labelling, Data and telecommunications labelling, Electrical labelling, General identification, Inventory and inspection labelling, Laboratory labelling, Solar Panel labelling, Tamper Indicating Labels, Warehouse marking, Wire and cable labelling

Materials Supported: Diesel-resistant Heat-shrink Polyolefin Sleeve, Direct Thermal Paper, FreezerBondz™ Polyester, Heat-shrink Polyolefin, High Temperature Heat-shrink Polyvinylidene Fluoride Sleeve, Metallic, Non-metal Polyester, Metallised Polyester, Nylon Cloth, Paper, Polyester, Polyethylene Foam Laminate Polyester, Polyethylene Tag, Polyimide, Polypropylene, Polyvinylfluoride, Repositionable Paper, Self-laminating Polyester, Self-laminating Vinyl, StainerBondz™ Polyester, Static Dissipative Polyester, Tamper-evident Metallised Polyester, Tamper-evident Polyester, Tamper-resistant Metallised Vinyl, Tamper-resistant Vinyl, Vinyl, Vinyl Cloth

Colour: Blue, Grey

DIMENSIONS

Printer dimensions: 292.10 mm (W) x 370.84 mm (H) x 530.86 mm (D)

Weight: 18.14 kg

Core - Diameter: 76.20 mm

Display size: 177.80 mm

Minimum Label Height: 3.18 mm

Minimum Label Width: 4.01 mm

PRODUCT FEATURES

Auto Shut Off: Yes

Battery Type: Coin/Button Cell, Internal, not removable

Language Support: EBahasa (Indonesian), Bahasa Malay, Bulgarian, Chinese (Traditional & Simplified), Croatian, Czech, Danish, Dutch, English (US), Estonian, Finnish, French (Canada), German, Hungarian, Japanese, Korean, Norwegian (Bokmål), Polish, Portuguese, Romanian, Russian, Slovak, Spanish (Universal), Thai, Turkish, Vietnamese

Calibration: Automated with i75-Series Consumables

Connectivity Options: Bluetooth, Ethernet, USB, Wi-Fi

Custom Labels: Available

Cutter: Auto Cutter (cut off), Auto Cutter (perf cut)

Display Type: Colour LCD Touchscreen

Hardware Options: Auto cutter, Cleaning swabs, I/O interface accessory, Narrow width print rollers, Printhead (300 dpi), Printhead (600 dpi)

Battery: Shipped installed in equipment

Interface Type: Touchscreen & PC

Internal Memory Capacity: 512 MB RAM, 195 MB IFFS Flash

Barcode Symbolologies: Code 39, Codabar, Code 128, Code 128A, Code 128B, Code 128C, Code 39 Full ASCII, Code 93, Code 93 Full ASCII, EAN-13, EAN-13 Extension 2, EAN-13 Extension 5, EAN-8, EAN-8 Extension 2, EAN-8 Extension 5, GS1-128, HIBC, Industrial 2 of 5, ITF-14, JAN-13, JAN-13 Extension 2, JAN-13 Extension 5, JAN-8, More through Brady WorkStation, More through software, UPC-A, UPC-E, Aztec, Data Matrix, GS1 DataMatrix, MicroPDF417, PDF417, QR code

Keyboard Type: None

Operating Humidity Range: 10%-85% (RH non-condensing)

Operating System: Windows® 10, Windows® 11, Windows® 8.1, Windows® Server 2012, Windows® Server 2012 R2, Windows® Server 2016

PRODUCT FEATURES

Operating Temperature: 10°C - 40°C

Stand Alone Printing: Mobile device connected, Stand-alone & Peripheral

Power Source: Outlet

Power Supply Voltage: 100 - 240 V @ 50 - 60 Hz

Print Preview Feature: Yes

Storage humidity: 15%-90% (RH non-condensing)

Storage Temperature: -20°C - 50°C

Units: Inches, Millimetres, Points

Cut Options Available: Cut at the end of print jobs, Cut between labels

PRINTING SPECIFICATIONS

Print Technology: Direct Thermal, Thermal Transfer

Print Speed: 304.80 mm/s

Printing Functions: Autocut material (accessory required), Perforation (accessory required), Tear-off print

Colour Capability: Monocolour

Resolution: 300 dpi (600 dpi version also available)

Display Resolution: 1024 x 600 pixels

Max. Label Width: 108.97 mm

Max. Liner Width: 114.05 mm

Recommended Usage per day: 7000

Max. Print Width: 105.66 mm

Max. Print Length: 1.524 m

Max. Roll Outer Diameter: 215.90 mm

Max. Label Thickness: 1.956 mm

Hours of Operation: 24 hours/7 days

No. of stock parts: 4500+ standard parts

Onscreen indicators: Bluetooth Status, Data Reception, Digital Clock, Error Messaging, Ethernet Status, i75 Smart material / Manual Material, Label dimensions, Print Job Preview, Ready state, Ribbon and label part number recognition, Supply Remaining, USB Connection, User-defined Printer Name, WiFi

Min. Label Width: 4.01 mm

Programming Language: ZPL Emulator

Smart cell: Yes

COMPATIBILITY

Continuous vs Die Cut Labels: Bulk, Custom

Min. Label Length: 3.18 mm

Min. Liner Width: 9.09 mm

COMPLIANCE

UNSPSC: 45101519

RoHS Compliance Status: Compliant with Directive 2011/65/EU and 2015/863

REACH SVHC Status: Part contains an SVHC

Approval/Compliance: CE

CONTACT US TO DISCUSS:

T +44 (0)1484 556996 E sales.iq@bowe.com

bowe.com/iq

BOWE IQ, Underbank Mills, Dunford Road, Holmfirth, West Yorkshire HD9 2AR



Follow us on LinkedIn

